TitanHP™


MHP7960-500-1
Selection Valve, 2 Position/10 Port

Description

The MHP7960-500-1 is a DuraLife® processed stainless steel 2-position, 10-port motorized valve. This valve includes a circuit board. This board is referred to as the Motor Driver/Valve Controller Board and is programmed for 1-line level control. The design of this valve provides a small footprint.



Flow Diagram:
A schematic of the valve flow switching pattern is shown to the right. The numbered circles represent the ports in the valve stator and stator face assembly. The grooves represent the connecting passages in the rotor seal. Please note that this is a representation of the flow path and may not show the true position of the ports and grooves.



Specifications


- **Liquid Contacts:** DuraLife® an SPC-1 coated stainless steel stator with Vespel blend rotor seal.
- **Connections:** Accepts 10-32 UNF-2B male threaded fittings
- **Flow Passage Diameters:** 0.25mm (0.010”)
- **Port-to-Port Volume:** 500nL
- **Operating Pressure:** Maximum pressure 414 bar (6,000 psi, 41 MPa).
- **Operating Humidity:** <95% humidity, non-condensing
- **Shipping and Storage Temperature:** Shipping, storing or operating this valve below 0°C with water in the fluid passages may cause failure of the sealing surfaces.
- **Regulatory REACH and RoHS Compliance Information**: Yes

IDEX HEALTH & SCIENCE

For ordering, technical support, and contact information please visit www.idex-hs.com

Dimensional l Drawings
Dimensions are in inches [millimeters]
For Reference Only

NOTE: DuraLife® is not recommended for use with solutions containing formic acid.



HEALTH & SCIENCE

For ordering, technical support, and contact information please visit www.idex-hs.com